EN

FLOW-SMS
Gas flow

FS-102C

Surface Mount Sub-System Mass Flow Meter



Bronkhorst®

Technical specifications

Measurement & control

Type of media	Gases
Flow range	min. 0.08…4 l_n/min max. 1…50 l_n/min
Accuracy	±0.5% Rd plus ±0.1%FS
Repeatability	<±0.2% Rd (or <±0.04% FS whichever is greater)
Turndown ratio	up to 1:187.5 (1:50 in analog mode)
Multi fluid capability	storage of max. 8 calibration curves
Control stability	< ± 0.1% FS (typical for 1 ln/min N2)
Response time (sensor)	typical 0.5 sec
Operating temperature	-10…+50°C
Temperature sensitivity	zero: < 0.05% FS/°C; span: < 0.05% Rd/°C
Leak integrity, outboard	Instruments < 2 x 10^{-9} mbar l/s He (vacuum tested) Total assembly < 10^{-6} mbar l/s He (leak tested at 15 barg against atmosphere)
Pressure sensitivity	0.1% Rd/bar typical N2; 0.01% Rd/bar typical H2
Mounting	max. error at 90° off horizontal 0.2% at 1 bar, typical N2
Warm-up time	30 min. for optimum accuracy
Storage/transport conditions	0...+50°C, max. 95% RH (non-condensing)

Approvals

Marking	CE, RoHS, WEEE, REACH

Mechanical specs

Pressure rating (PN) - in barg	10
Ingress protection	IP40
Material wetted parts	stainless steel 316L or comparable
Sealing material	standard: FKM/Viton®; options: EPDM, FFKM/Kalrez®, FDA and USP Class VI approved compounds
Weight	0.6 kg

Electrical properties

Power supply	+15…24 Vdc
Power consumption	1.5 W typical at 24 V for fieldbus: add + 0.9 W
Analog output	0…5 (10) Vdc or 0 (4)…20 mA (sourcing)
Analog setpoint	0…5 (10) Vdc or 0 (4)…20 mA (sinking)
Digital communication	standard: RS232 options: CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK, FLOW-BUS

Electrical interfaces

Power (main connector)	9-pin D-sub (male)
Function (instrument connector)	Analog, RS232
PROFIBUS DP	9-pin D-sub (female)
CANopen / DeviceNet	5-pin M12A (male)
Modbus RTU/ASCII/FLOW-BUS	RJ45
Modbus TCP / EtherNet/IP / EtherCAT®/ PROFINET / POWERLINK	2x RJ45

Last modified 13-11-2026.
© Bronkhorst High-Tech B.V. All rights reserved.

The specifications are subject to change without notice. The products described herein and this document are subject to specific legal disclaimers as set forth on www.bronkhorst.com/disclaimer. For more information and detailed advice, please contact the local Bronkhorst sales partner. Contact details can be found at www.bronkhorst.com/contact.